# POLAR SERIES



**POLAR 2-95** 

Option 2 x 850 mm seal





3 x 1100 mm seal

• Capacity pump 300 m3/h

1100 mm

- Machine cycle 15-40 sec.
- Dimensions 1210 x 2420 x 1130 mm
- Weight 767 kg
- Voltage 400V-3-50Hz (Other voltages available)
- Power 7,0 9,0 kW



# POLAR SERIES

# FAST AND ROBUST VACUUMPACKAGING MACHINES WITH WORLD WIDE REPUTATION

- Renowned series of stainless steel packaging machines for industrial applications
- Complete range for vacuum and MAP packaging solutions
- Extensive program choices for specific packaging requirements
- User friendly and low maintenance supplied with complete service program
- Hygienic and Intelligent Design
- Fully HACCP compatible

# **FOOD PRODUCTS**

Industrial Production - Wholesale - Export Packaging (meat, poultry, fish, cheese, vegetables etc.)

- No contamination or bacteria's multiplication, hence an extended shelf life resulting in:
- cost savings (larger purchasing orders, efficient cooking time spreading and diminution of products losses)
- turnover increase (more variation and spread in product range)
- Optimal product and storage hygiene (hermetically sealed)
- No loss of product (prevents drying out, moulds and freeze burn)
- Improved product quality (product maturing in packaging, no loss of aroma)
- Professional product presentation
- Optimal packaging contributes to food safety and HACCP standards

## NON-FOOD PRODUCTS

Electronics - Semi-conductors - Metal - Pharmaceutical Products - Textiles - Laboratories etc.

- Moisture free anti-corrosive packaging
- Air and dust-free antistatic packaging
- Volume reducing packaging
- Product protecting and fraud resisting packaging

# (









# SPECIFICATIONS

#### GENER

- Single and double chamber floor models
- · Stainless steel housing
- Stainless steel flat working plate
- Stainless steel lid
- Easily removable silicon holders for cleaning working plate
- Sealing mechanism mounted in lid
- Insert plates for adjusting vacuum chamber height

## PACKAGING FUNCTIONS

Vacuum

Optimal final vacuum 99,99% (0,1 Mbar)

Gas-flush

Injecting food-gas for product protection and longer shelf life

Soft-air

Controlled ventilation for protection of product and packaging

# SEALING SYSTEMS

Double Seal

2 x 3.5 mm convex sealing wire for optimal moisture elimination (double protection)

Trennsea

1 x 3.5 mm convex sealing wire + 1 x 1.1 mm round cutting wire / One time setting (cut off remaining flap)

• 1-2 Trennseal

1 x 3.5 mm convex sealing wire + 1 x 1.1 mm round cutting wire / Independent time setting (shrink bags)

Wide Seal

1 x 8.0 mm flat sealing wire

Bi-Active Seal

Upper and lower sealing bars with 1 x 5.0 mm flat sealing wire (thick and aluminium vacuum bags)

# **OPERATIONAL CONTROL FUNCTIONS**

Digital Control

Time control / Automatic programming / 10 default programs

Sensor Control

Set percentage pressure for vacuum and gas functions for accurate and constant packaging results / Automatic programming / 10 default programs / Vacuum plus time

• Liquid Control

Set percentage pressure for vacuum and detect boiling point of the product. For fast cycle and better food protection

• Advanced Control System

Set percentage pressure or mbar/hPa for vacuum and gas function for accurate and constant packaging results / 20 default alphanumeric programs / Vacuum plus time / Sequential vacuum / Secured Operator Access / HACCP track and trace function / LCD full color screen / PC interface / Compatible with label printer

## SUPPORT CONTROL FUNCTIONS

- STOP button for partial/full cycle interrupt
- Digital maintenance program for pump / Operating hours counter / Service indicator programs / Sleeper function etc.

# **OPTIONAL FUNCTIONS / ACCESSORIES**

- Service kit for standard maintenance
- Special control options for specific applications



Optional

Standard

Sentence and printing errors reserved